
















<b>TECNARIA FIX</b>	CALCESTRUZZO	LAMIERA	LEGNO	CALCESTRUZZO ALLEGGERITO	SUPPORTI CRITICI
	ASTL con R45 (60 ÷ 665 mm)*				
	ASTL con R75 (60 ÷ 665 mm)*				
	BN 5.6 (28 ÷ 160 mm)				
	CAT 4.5 (28 ÷ 75 mm)				
	CAT 6.0 (50 ÷ 350 mm)				
	CS 6.1 (28 ÷ 200 mm)				
	FMHD 6.0 (30 ÷ 300 mm)	FMHD 6.0 (30 ÷ 300 mm)	FMHD 6.0 (30 ÷ 300 mm)		
		PS 4.8 (40 ÷ 200 mm)			
		BS 4.8 (50 ÷ 300 mm)			
		DBTA 4.8 (60 ÷ 240 mm)			
		XHD 6.7 (32 mm)			
		FMBS 5.5 (40 ÷ 205 mm)			
			LBS 6.0 (50 ÷ 240 mm)	LBS 6.0 (50 ÷ 240 mm)	
					FLOW 5.0 (50 ÷ 190 mm)
					FLOW 6.4 (35 ÷ 190 mm)

\* riferito allo spessore di isolante fissabile



SP-70-D




SP-70-F



SP-70-S



SP-70-CP



SPA-7070-D



SP-8240-D



SP-8240-F



SP-8240-S



SPB-8240-D



SPCP-80-F2



SPCP-80-F4